

**THE JUNIPER
CF34-10E ENGINE
WASH PROBES**
JMP/CF34/D/6932

(Supplied as set of two)


Fitment Guide



AIRCRAFT SERVICE EQUIPMENT



The CF34-10E long engine wash probes **JMP/CF34/D/6932**





Juniper's high capacity compressor washing rigs



The 2x25 gallon rig
(JMP/CFM56/D/4777/C200)
NSN 1730-99-668-7936

The 2x50 gallon rig
(JMP/LUFT/D/4972/C500)

Delivery hose selection




When using CF34-10E engine wash probes, turn the three way selector to position 'B' this ensures selection of the ½" bore delivery hose.


Please refer to the relevant AMM for correct flow rate information.

STEP 1: Locating the probes


Caution: Ensure that the engine fan is held securely during the fitting of the engine 'j' hook probes.



Each probe to be inserted and fitted on the engine at approximately the **3 & 9 o'clock** positions so that the probe 'j' hook fits over the booster / fan splitter.



STEP 2: Securing the spring loaded clamps



The clamp tightened approximately 5mm inside the edge of the translating sleeve.

Each probe has a single spring loaded clamp which is tensioned against the edge of the engine translating sleeve.

For first time fitment to the engine, loosen the tube clamp via the four allen key bolts and dummy fit the probe to the engine. Once the hook is positioned, visually line up the back edge of the clamp with the edge of the translating sleeve (without hooking it over) and carefully slide the clamp forward a further 5mm (approx.) along the probe tube. Re-tighten the allen key bolts.

Then, using the handle, pull the clamp towards you and hook it gently over the translating sleeve edge until it rests securely against the rubber lining. You should feel the clamp springs tensioning as you hook it over.

Note: *If you are unable to pull the clamp far enough to hook over the sleeve, then the clamp has been positioned too far forward, and if you feel no tensioning of the clamp springs as you hook it over, then the clamp has not been moved forward far enough. In both cases, loosen off the allen key bolts and re-position the clamp before re-tightening and trying again.*

Once the clamps have been positioned correctly they should not require re-adjusting. To remove the clamp simply pull the handle towards you and unhook it from the translating sleeve.

Connect the twin hose assembly (provided with all compressor wash rigs) to both of the engine probes, making sure

that the probes are attached securely to the engine with the hoses attached, then connect delivery hose from the wash rig to the twin hose assembly.

Probe installation is now complete.

Please refer to the relevant AMM for flow rate information.



Note: *Images used in this guide are for illustrative purposes only and may not accurately represent the engine in question.*

Contact details



Contractors to
H.M. Government Departments
Registered with ISO 9001:2015

A.T. Juniper (Liverpool) Limited

Aircraft Service Equipment

Head Office:

Marshall Works, 5-17 Bleasdale Road, Allerton,
Liverpool L18 5JB, United Kingdom

Tel: +44 (0)151 733 1553

Fax: +44 (0)151 734 3166

Email: gse@juniper-liverpool.com

Web: www.juniper-liverpool.com

Also At:

Ash House, Prenton Way, North Cheshire Trading Estate,
Wirral CH43 3DU, United Kingdom